



## Tasmanian Timber Flooring Options

*Quality strip & overlay Tasmanian timber flooring is the ideal product for your home or office.*

### Tasmanian Oak Appearance Grades

Durable and incredibly stable, Tasmanian Oak flooring is available in two aesthetically beautiful grades – Prime and Classic. Tasmanian Oak Classic is a high feature grade, visually enhanced by the natural characteristics of timber. Tasmanian Oak Prime provides minimal feature.

### Quality Assured

Flooring from Tasmanian Timber suppliers is machined, finished and packaged to the highest quality under Australian Standard AS2796.2, and certified sustainable by Responsible Wood. It is also independently audited by the Centre for Sustainable Architecture with Wood at the University of Tasmania for specified grade, moisture content, form and compliance.

### Important Installation Tips

Solid timber strip flooring is the ideal selection to produce a beautiful and long lasting floor. Correct installation is essential to realise its full potential.

### Installation Guides for Tasmanian Timber Flooring

Installation guides for overlay strip flooring and solid timber flooring on joists are available from your Tasmanian Timber Flooring Supplier or online at: [tasmaniantimber.com.au](http://tasmaniantimber.com.au).

### Gluing


The glues used to adhere timber flooring must be specialist elastomeric glues. Glues that set hard (such as contact or general building adhesives) are not suitable and can lift off the substrate.

### Floating


Floating floors are not fixed to the substrate and are held down by skirtings.

### Nailing

Building regulations govern the size and number of nails used to fix strip flooring to joists. Boards over 85 mm wide MUST be surface nailed. Only boards 85 mm wide or less can be secret nailed. Overlay and panel floors should be nailed in accordance with the manufacturer's instructions.



Surface Nailed



Secret Nailed













[tasmaniantimber.com.au](http://tasmaniantimber.com.au)

ORIGINAL

TASMANIAN  
TIMBER™

# Tasmanian Timber Flooring Options

|                              | Flooring →                                                                          | Standard Strip Flooring                                                                   | Overlay Strip Flooring                                                                         | Pre-Finished Engineered Flooring                                                       | Block Parquetry                                                                                                     | Finger Parquetry                                                                                                    |
|------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Substrate ↓                  |                                                                                     | Quality tongue and groove flooring, usually 19 mm thick. Widths range from 60 to 133 mm.* | Quality tongue and groove flooring, usually 12 – 14 mm thick. Widths range from 60 to 112 mm.* | Engineered prefinished flooring with an attractive, hard wearing solid timber surface. | Pieces of solid timber ready to lay in a range of patterns.                                                         | Small pieces of solid timber ready to lay sheets or with a mesh backing.                                            |
|                              |                                                                                     |          |               |      | <br>other patterns are available | <br>other patterns are available |
| Joists                       |   | ✓<br>Nail                                                                                 |                                                                                                |                                                                                        |                                                                                                                     |                                                                                                                     |
| Sheet Flooring on Joists     |  | ✓<br>Nail or Glue                                                                         | ✓<br>Nail or Glue                                                                              | ✓<br>Floating                                                                          | ✓<br>Glue                                                                                                           | ✓<br>Glue                                                                                                           |
| Concrete                     |  | ✓<br>Glue                                                                                 | ✓<br>Glue                                                                                      | ✓<br>Floating                                                                          | ✓<br>Glue                                                                                                           | ✓<br>Glue                                                                                                           |
| Plywood Underlay on Concrete |  | ✓<br>Nail or Glue                                                                         | ✓<br>Nail or Glue                                                                              | ✓<br>Floating                                                                          | ✓<br>Glue                                                                                                           | ✓<br>Glue                                                                                                           |
| Battens on Concrete          |  | battens to 450 centres<br>✓<br>Nail                                                       |                                                                                                |                                                                                        |                                                                                                                     |                                                                                                                     |

## Notes

\* Only boards to 85 mm wide or less can be secret nailed.



[tasmaniantimber.com.au](http://tasmaniantimber.com.au)

ORIGINAL

TASMANIAN  
TIMBER™